



## JA-157P Dual zone outdoor wireless motion detector - curtain

The JA-157P wireless outdoor detector with curtain lens characteristics is designed to **indicate disturbances outside the building caused by human bodies**.

○ [Declaration of conformity - JA-157P \(PDF 315.65 kB\)](#)

### Description

It is a dual zone outdoor detector by Optex with a 5° angular width detection zone which makes it very suitable for guarding narrow spaces such as balconies, French doors, terraces, etc.

It is supplemented with a transmitter compatible with the JABLOTRON 100+ system. The device is equipped with dual-beam optics with a high immunity against false alarms and the detection of small animals. The detector has an anti-masking function - i.e. protection against shielding its view.

The detector is also equipped with three tamper contacts. One on the detecting part and the next two on the transmitter part with both of them immediately reporting tampering of the detector or removal from the installation place.

### Technical specifications

<b>Power</b>	1x Lithium battery type CR123A (3.0 V/1.4 Ah) Please note: Battery is not included
<b>Current consumption (nominal/maximal)</b>	30 µA/53 mA
<b>Typical average battery lifetime</b>	approx. 3 years (120 s saving mode)
<b>Communication band</b>	868.1 MHz, Jablotron protocol
<b>RF range - distance from the CP</b>	up to 300 m (open area)
<b>Optex detector parameters</b>	
<b>Detection characteristics</b>	2 or 5 m/5°
<b>Installation height</b>	0.8 - 1.2 m
<b>Object motion speed</b>	0.3 - 1.5 m/s
<b>Detector cover conformance</b>	IP55
<b>Operational environment</b>	IV according to EN 50131-1

<b>Operational temperature range</b>	-20 °C to +60 °C
<b>Max. relative humidity</b>	95 %
<b>Security grade</b>	according to OPTEX
<b>Complies with</b>	ETSI EN 300 220, EN 50130-4, EN 55022, EN 60950-1
<b>Dimensions</b>	52 x 176 x 66 mm
<b>Weight</b>	180 g
<b>Can be operated according to</b>	ERC REC 70-03